



- Surprisingly light weight yet robust
- Color coding for easy identification





Special engineering plastics resulting in better protection against chemical and physical corrosion



Fully autoclavable



Enhanced UV resistance for higher durability



Calibrated in ISO 17025 accredited laboratory.

Supplied with individual QC and calibration report according to ISO 8655










- Ergonomic design
- Light & smooth plunger action
- Soft feel handle grip
- Suitable for both left and right hand users

One of the lowest operating force
 requirement compare to most of the pipettes



 Special Teflon® sealing mechanism in lieu of conventional O-ring resulting in long lasting precise and smooth operation



 Pipette handle has coating of Thermoplastic Elastomer which prevents transfer of body heat to the pipette ensuring high accuracy even during continuous use



- Large and clear 4 digit display giving smaller increments for wider volume selection options
- Resistance free click stop counter
- Volume display is always visible while pipetting



- Soft touch tip ejection
- Locking mechanism for preventing accidental volume changes




- In house cleaning, repair and calibration possible without any special tools
- Easily accessible recalibration mechanism



 Shelf mounting stand for convenient storage and handling







- Specially designed tip cone with O-ring resulting in:
 - □ Leak free operation
 - □ Smooth and light loading and ejection
 - □ Choice of variety of tips



Includes all innovative features of Smart single channel pipette







Variable Volume Micropipette

Cat. No.	Volume Range [μl]	Increments [µl]
SVA-125	0.1-2.5	0.002
SVA-100	0.5-10	0.02
SVA-200	5-50	0.1
SVA-500	10-100	0.1
SVA-600	100-1000	1
SVA-700	2-20	0.02
SVA-800	20-200	0.2
SVA-905	500-5000	10
SVA-1000	1000-10000	20

8 Channel Micropipette

Cat. No.	Volume Range [µl]	Increments [µl]
SMA8-010	0.5 - 10 μΙ	0.02
SMA8-020	2 - 20 μΙ	0.02
SMA8-050	5 - 50 μΙ	0.1
SMA8-100	10 - 100 μΙ	0.1
SMA8-200	20 - 200 μΙ	0.2
SMA8-300	30 - 300 μΙ	0.2

12 Channel Micropipette

Cat. No.	Volume Range [μl]	Increments [µl]
SMA12-010	0.5 - 10 μΙ	0.02
SMA12-020	2 - 20 μΙ	0.02
SMA12-050	5 - 50 μΙ	0.1
SMA12-100	10 - 100 μΙ	0.1
SMA12-200	20 - 200 μΙ	0.2
SMA12-300	30 - 300 μΙ	0.2

Pipette Stand

Cat. No.	Description	
SAS-01	Carousel stand for 6 pipettes	
SAS-02	Shelf mount pipette holder	

Fix Volume Micropipette

Cat. No.	Volume [µl]
SFA-205	2.5
SFA-5	5
SFA-10	10
SFA-20	20
SFA-25	25
SFA-50	50
SFA-100	100
SFA-200	200
SFA-250	250
SFA-500	500
SFA-1000	1000
SFA-2000	2000
SFA-5000	5000
SFA-10000	10000



