

TRULY EFFORTLESS PIPETTING




Accumax Fab Pipette



Magnet assisted piston for consistently precise results



Innovative spring and seal design for one of the lowest plunge force requirement




Corrosion resistant tip ejector with unique shock absorbing mechanism



Volume lock setting



Fully autoclavable, ergonomic design



Easy in-house calibration



Highly durable PVDF tip cone



For more details visit us at www.accumaximum.com

Accumax Fab Pipette

Variable Volume

Cat. No.	Volume Range [μl]	Increments [μl]	Test Volume [μl]	Inaccuracy (\pm) %	Imprecision (\pm) %
AFV-2.5	0.1-2.5	0.002	0.25	12	6
			1.25	2.5	1.5
			2.5	2.5	0.7
AFV-10	0.5-10	0.02	1	2.5	1.5
			5	1.5	0.8
			10	1	0.4
AFV-20	2-20	0.02	2	3	1.5
			10	1.2	0.6
			20	0.9	0.3
AFV-50	5-50	0.1	5	2	2
			25	0.8	0.4
			50	0.6	0.3
AFV-100	10-100	0.1	10	3	1
			50	1	0.3
			100	0.8	0.2
AFV-200	20-200	0.2	20	2.5	0.7
			100	0.7	0.3
			200	0.6	0.2
AFV-1000	100-1000	1	100	3	0.6
			500	1	0.2
			1000	0.6	0.2
AFV-5000	500-5000	10	500	2.4	0.6
			2500	1.2	0.25
			5000	0.6	0.2
AFV-10000	1000-10000	20	1000	3	0.6
			5000	0.8	0.2
			10000	0.6	0.15